



Openwell Submersible Pumps - Horizontal

Horizontal Openwell (Three Phase)

Product Code	hp/kW	Size (mm)		Head in Meter											
				10	15	20	22.5	24	26	30	35	40	42	44	50
LNHSM7 BB	3.0/2.2	50	Discharge in LPM	740	700	680	640	550	460	280	–	–	–	–	–
LNHSM7 BB DD	3.0/2.2	50		740	700	680	640	550	460	280	–	–	–	–	–
LNHSM7 CO EE	3.0/2.2	50		720	690	660	620	540	450	260	–	–	–	–	–
LNHSM7 CO EE HD	3.0/2.2	50		700	680	640	600	560	460	280	–	–	–	–	–
LNHSM7 CO HE	3.0/2.2	50		720	690	660	620	540	450	260	–	–	–	–	–
LNHSM7 CO MS EE	3.0/2.2	50		720	690	660	620	540	450	260	–	–	–	–	–
LNHSM7 CO MS HD EE	3.0/2.2	50		700	680	640	600	560	460	280	–	–	–	–	–
LNHSM7 CO MS HE	3.0/2.2	50		720	690	660	620	540	450	260	–	–	–	–	–
LNHSM9 BB DD	3.0/2.2	65		1060	920	760	590	500	–	–	–	–	–	–	–
LNHSM9 CO MS HE	3.0/2.2	65		1040	900	740	570	480	–	–	–	–	–	–	–
LNHSM10 BB	5.0/3.7	50		860	830	780	740	720	610	570	540	510	330	–	–
LNHSM10 BB DD	5.0/3.7	50		860	830	780	740	720	610	570	540	510	330	–	–
LNHSM10 CO EE	5.0/3.7	50		840	800	760	740	700	600	560	520	500	310	–	–
LNHSM10 CO HD EE	5.0/3.7	50		820	780	740	720	680	600	570	540	520	330	280	–
LNHSM10 CO HE	5.0/3.7	50		840	800	760	740	700	600	560	520	500	310	–	–
LNHSM10 CO MS EE	5.0/3.7	50		840	800	760	740	700	600	560	520	500	310	–	–
LNHSM10 CO MS HD EE	5.0/3.7	50		820	780	740	720	680	600	570	540	520	330	280	–
LNHSM10 CO MS HE	5.0/3.7	50		840	800	760	740	700	600	560	520	500	310	–	–
LNHSM13 BB	5.0/3.7	65		1300	1100	920	880	810	740	630	–	–	–	–	–
LNHSM13 BB DD	5.0/3.7	65		1300	1100	920	880	810	740	630	–	–	–	–	–
LNHSM13 CO EE	5.0/3.7	65		1250	1000	900	860	800	720	630	–	–	–	–	–
LNHSM13 CO HE	5.0/3.7	65		1250	1000	900	860	800	720	630	–	–	–	–	–
LNHSM13 CO MS EE	5.0/3.7	65		1250	1000	900	860	800	720	630	–	–	–	–	–
LNHSM13 CO MS HE	5.0/3.7	65		1250	1000	900	860	800	720	630	–	–	–	–	–
LNHSM16 BB HD	7.5/5.5	50		–	–	–	920	880	870	820	780	740	700	630	520
LNHSM16 CO	7.5/5.5	50		–	–	–	880	860	840	800	760	720	680	600	450
LNHSM18 CO	7.5/5.5	65		–	1350	1120	1000	980	900	860	800	740	–	–	–

Horizontal Openwell

Product Code	hp/kW	Size (mm)	Frame		Head in Meter															
					10	15	17.5	20	22.5	24	27.5	30	35	37.5	40	42	45	50	55	60
LNHSM14	5.0/3.7	75	BB	Discharge in LPM	1440	1300	1100	1030	990	–	–	–	–	–	–	–	–	–	–	–
LNHSM16	7.5/5.5	50	BB		–	–	–	–	880	860	840	820	760	740	720	690	650	500	300	–
LNHSM18	7.5/5.5	65	BB		–	1400	1350	1200	1100	980	900	820	800	–	–	–	–	–	–	–
LNHSM19	7.5/5.5	75	BB		1600	1510	1420	1340	1200	1000	–	–	–	–	–	–	–	–	–	–
LNHSM20	10.0/7.5	65	BB		–	1510	1410	1350	1250	1020	1000	940	900	740	–	–	–	–	–	–
LNHSM21	10.0/7.5	50	BB		–	–	–	–	980	900	880	860	830	780	740	720	700	660	460	320

Horizontal Openwell - HHD Model

Product Code	hp/kW	Size (mm)	Frame		Head in Meter															
					10	15	20	22.5	24	27.5	30	35	37.5	40	45	50	55	60		
LNHSM7 HHD	3.0/2.2	50	BB	Dis. in LPM	820	740	730	700	680	580	540	480	460	280	–	–	–	–		
LNHSM10 HHD	5.0/3.7	50	BB		860	840	820	780	740	620	580	540	500	400	310	220	–	–		
LNHSM16 HHD	7.5/5.5	50	BB		–	–	–	900	880	860	820	780	740	700	680	600	420	300		



Openwell Submersible Pumps - Vertical

Vertical Openwell

Product Code	hp/kW	Stage	Size (mm)		Head in Meter															
					10	15	20	30	35	40	45	50	55	60	65	70	80	100	120	
LNHSM7V	3.0/2.2	2	50	Discharge in LPM	720	700	600	440	300	–	–	–	–	–	–	–	–	–	–	
LNHSM13V	5.0/3.7	2	65		1100	920	850	770	600	400	–	–	–	–	–	–	–	–	–	
LNHSM10V	5.0/3.7	3	50		800	720	690	600	580	500	440	300	220	–	–	–	–	–	–	
LNHSM18V	7.5/5.5	3	65		–	1100	940	900	860	800	770	620	560	400	–	–	–	–	–	
LNHSM16V	7.5/5.5	4	50		–	800	720	680	650	600	580	500	480	440	350	220	–	–	–	
LNHSM20V	10/7.5	4	65		–	–	1200	940	920	900	880	800	760	680	640	560	400	–	–	
LNHSM28V	12.5/9.3	5	65		–	–	1400	1300	1100	940	920	900	880	800	780	760	700	560	–	
LNHSM31V	15/11	6	65		–	–	1550	1460	1300	1200	1000	980	940	900	880	820	780	700	560	